

I 28514-66

ACC NR: AR6000074

that required for the breakdown of thin dielectric films. This indicates the importance of impact ionization and the development of electron avalanches. The oscillograms registered repeated short-period breakdown of selenium rectifiers, after which the properties of the rectifiers were restored. Refs.: 17. (Translation (S.A.)

SUB CODE: 09/ SUBM DATE: none

Card 2/2 CC

Zitokhovskiy, M. K.

PROGRESSIVE AND RECESSIONARY INFLATION


*Effect of the Mechanical Properties of the Metal, of its Composition, and of the Coefficient of Strength on the Elastic Properties of Bourdon Tubes. M. K. Zhukovskiy (Tzchn. Indust. (Precision Ind.), 1927, (10), 13-16; (12), 12-15).—[In Russian.] For tubes made from "L-03" brass, relations were established between the limit of proportionality, tensile strength, and elongation, and between the tensile strength on the one hand, and movement of the tube's end, pressure applied, and strength coeff. (i.e. the ratio of the limit of proportionality to the pressure limit of the pipe) on the other. A tensile strength of 80-85 kg./mm.² and an elongation of 6-10% are recommended. The alloys: (1) copper 62, zinc 38%, (2) copper 80, nickel 20%, (3) copper 93, zinc 3, tin 4%, and (4) copper 94.5, beryllium 1-0.8% may be used if the size of the tube is correctly chosen. The strength coeff. must not be less than 2. The ratio of the axes of elliptical pipes may be between 3.7 and 8.—N. A.

卷之三

PARALITERATURE, CLASSIFICATION

APPROVED FOR RELEASE: 09/19/2001

CIA-RDP86-00513R002064910003-6"



ZHOKHOVSKII, M.K.
PHASE I Treasure Island Bibliographic Report

REF ID: A660000031

Call No.: AF-480616, Incl. 7

BOOK

Author: ZHOKHOVSKII, M.K.

Full Title: TECHNIQUES OF MEASURING PRESSURE AND RARIFICATION

Transliterated Title: Tekhnika izmereniiia davleniiia i razriazheniiia

Publishing Data

Originating Agency: Committee dealing with measures and measuring instruments
at the Council of Ministers of the USSR.Publishing House: State Publishing House of Scientific-Technical Literature on
Machine Building.

Date: 1952.

No. pp.: 270

No. copies: 6,000

Editorial Staff

Editor: Lisachenko, I.P.

Technical Editor: None.

Editor-in-Chief: None.

Appraiser: Dolinskii, E.T.,
B. Eng. Sc.

Text Data

Coverage: The book describes the theories of various apparatuses and devices
for measuring pressure and rarification; also, describes the con-
struction characteristics of major components, methods of calibration,
testing, and operation. Data on the following types of apparatuses
given: apparatus with liquids, piston manometers, spring apparatus,
and combined electrical manometers.Purpose: A book for operation and testing engineers; and, a textbook for
students studying the science of measurement.

1/2

Card 2/2

0000031

Call No.: AF-480616, Incl. 7

Full Title: TECHNIQUES OF MEASURING PRESSURE AND RARIFICATION

Facilities: None.

No. Russian References: 30.

Available: A.I.D., Library of Congress.

ZHOKHOVSKIY, M.K.

Mercury fusion curves at pressures up to 10,000 kg/cm².
Izm.rekh.no.5:3-6 S-O '55. (MLRA 9:1)
(Pressure (Physics)) (Mercury)

05456
SOV/120-59-3-27/46

AUTHORS: Zhokhovskiy, M. K., Konyaev, Yu. S., and Levchenko, V.G.
TITLE: A Piston Pressure Gauge for use up to 20,000
Atmospheres (Forshnevoy manometr do 20 000 am)
PERIODICAL: Pribory i tekhnika eksperimenta, 1959, Nr 3,

pp 118-122 (USSR)

ABSTRACT: A pressure amplifier is used in the gauge, which is seen in Fig 1. The piston 1 fits closely in the cylinder 2, which is held in the double jacket 3. Cylinder 2 is held by screwed ring 4, which has an unbalanced area. The latter piston lies in cylinder 7, which is coupled to the low-pressure piston via a ball joint; this body 3 to make the two cylinders strictly coaxial. The head 10 contains a valve 11 and viewing ports, and holes for connecting a piston gauge 12 with load 13. A hole in 10 joins 12 to 11; this communication can be cut off. The indicator 14 is used to measure the position of the piston. (The gain of the multiplier Card 1/3 is about x 280). Fig 2 shows a system used to produce

05456
SOV/120-59-3-27/46

A Piston Pressure Gauge for use up to 20,000 Atmospheres

20,000 atm and to measure it exactly. The gauge 1 is coupled through a junction block 2 to a pressure amplifier 3, which is fed at low pressure by the unit 4, which includes a pump, a vessel holding liquid, a gauge, valves, and connecting tubes. The booster unit 5 produces the initial high pressure by means of another working fluid; this unit is shut off by means of the hydraulically operated valve 6. The screw press 7 adjusts the height of the piston and operates valve 6. Gauge 8 and valve 9 are used to measure the pressure produced by 7. The block 2 contains a calibrated manganin pressure gauge 10 on the high-pressure side. Glycerol containing 40% glycol is used as the main working fluid; it has an initial viscosity of 1.65 poise, does not crystallize, and has only a small pressure coefficient of viscosity. Fig 3 shows how the speed of the piston varies with pressure when the piston is properly lapped into the cylinder. The constants of the apparatus are given at the top right corner of p 121. The last part deals with some tests made to ensure that plastic deformation is absent at the highest pressure. There are

Card 2/3

05456

SOV/120-59-3-27/46

A Piston Pressure Gauge for use up to 20,000 Atmospheres

3 figures and 11 references, 7 of which are Russian,
2 English and 2 German.

ASSOCIATION: Laboratoriya fiziki sverkhvysokikh davleniy
AN SSSR (Laboratory of High-Pressure Physics, Academy
of Sciences of the USSR)

SUBMITTED: April 15, 1958

Card 3/3

24 (8)

06181
SOV/115-59-11-9/36

AUTHORS: Zhokhovskiy, M.K., Razumikhin, V.N., Zolotykh, Ye.V.,
Burova, L.I.

TITLE: A Thermodynamic Scale of High Pressures up to 25,000
 kg/cm^2

PERIODICAL: Izmeritel'naya tekhnika, 1959, Nr 11, pp 26-29

ABSTRACT: This article is based on a previous publication of the aforementioned authors [Ref 1]. At that time the authors investigated the curve of melting mercury up to 20,000 kg/cm^2 . They applied it for solving the problem of a high pressure scale. They confirmed experimentally that the extrapolation of the equation of the curve of melting mercury (on which the thermodynamic scale of pressure is base) is permissible up to 20,000 kg/cm^2 with an accuracy of 0.4-0.8%. In this article, the authors present the results of new investigations in a pressure range extended to 25,000 kg/cm^2 . The equipment for the experimental determination of the phase equilibrium of mercury and the methods of determining

Card 1/2

06181
SOV/115-59-11-9/36

A Thermodynamic Scale of High Pressures up to 25,000 kg/cm²

the equilibrium pressures and temperatures in the new pressure range up to 25,000 kg/cm², remained the same as in Ref 1. The thermodynamic scale of pressures was extended to 25,000 kg/cm² with an accuracy of $\pm 0.5\%$. A group of reference resistance pressure gages was developed which reproduce the thermodynamic scale of pressures within the aforementioned limits and with the aforementioned accuracy. A device was developed which may be used for transferring the values of the pressure scale to any device of high pressure engineering. This device consists of manually and mechanically operated hydraulic pumps, pressure multiplicators to 6000 and 25,000 kg/cm² and the necessary valve system as shown in Fig 2. In the interval between 5000 and 25,000 kg/cm², any intermediate value may be produced. There are 1 diagram, 1 graph, 1 table, and 3 Soviet references.

Card 2/2

ZHOKHOVSKIY, M.K.

Theory of manometers with a piston without packing. Trudy inst.
Kom. stand., ser i issn. prib. no. 46:5-29 '60. (MIRA 13:12)
(Manometer)

S/124/61/000/009/021/058
D234/D303

AUTHOR:

Zhokhovskiy, N.K.

TITLE:

Corrections of piston manometers caused by the influence of high pressures

PERIODICAL:

Referativnyy zhurnal. Mekhanika, no. 9, 1961, 98.
abstract 9 B729 (Tr. in-tov kom-ta standartov, mer.
i izmerit. priborov pri Sov. Min. SSSR, 1960, no.
46(106), 30-42)

TEXT:
In the process of measuring high pressures (of the order of 10000 - 20000 kg/cm²) by piston manometers it is necessary to make corrections owing to the deformation of the piston system of the manometer. The paper gives mathematical analysis and the deduction of a formula for calculating the magnitude of such corrections for manometers with a packless piston in a cylinder with back pressure and without back pressure, also for manometers with single and double differential piston. It is established that the correc-

Card 1/2

Corrections of piston manometers...

S/124/61/000/009/021/058
D234/D303

tion for piston manometers in its general form is a quadratic function of the pressure which is measured. Results of several investigations on the influence of pressure on the effective area of the piston of the manometer are exposed. [Abstracter's note: Complete translation]

Card 2/2

S/123/61/000/014/035/045
A004/A101

AUTHOR: Zhokhovskiy, M.K.

TITLE: Thermodynamic method of reproduction of superhigh pressures

PERIODICAL: Referativnyy zhurnal. Mashinostroyeniye, no. 14, 1961, 8, abstract
14E57 ("Tr. in-tov Kom-ta standartov, mer i izmerit. priborov pri
Sov. Min. SSSR", 1960, no. 46 (106), 68 - 80)

TEXT: The author substantiates the possibility of producing a thermodynamic pressure scale based on the equilibrium state of the liquid and solid phase of substances at a definite temperature and corresponding pressure. The author presents formulae describing the dependence of the critical temperature on the pressure for mercury, as well as experimental data confirming the correctness of the constants of this equation, and also the curves of the dependence of the specific melting energy on the temperature of various substances at pressures of up to 12,000 kgf/cm², and of the dependence of the specific melting energy on the pressure. A new form of the Simon equation is suggested and an interpretation of the physical significance of its constants is given. Tables of the

Card 1/2

Thermodynamic method ...

S/123/61/000/014/035/045
A004/A101

values of c-constant are given (ratio of the specific energy increment to the pressure increment) for various substances at pressures up to 12,000 kgf/cm² through every 1,000 kgf/cm². The conservation of the permanence of the c-constant at pressures of the order of 50,000 kgf/cm² has been confirmed by experiments. The extrapolation of the equation to realize the thermodynamic scale in the range exceeding 20,000 kgf/cm² is based on the physical interpretation of the constant and its analytic expression in terms of the melting parameter.

K. Perchikhin

[Abstracter's note: Complete translation]

Card 2/2

ZHOKHOVSKIY, M.K.; BAKHALOVA, V.V.

Errors due to deformations of piston manometers at pressures up to
10,000 kg-wt/cm². Izm.tekh. no.12:23-26 D '61. (MIRA 15:1)
(Manometer)

ZHOKHOVSKIY, M.V.

Some results of research in the field of high-pressure
measurements. Izm.tekh,no. 4:29-31 Ap '64. (MIRA 17:7)

ZHOKHOVSKIY, M.K.; BOGDANOV, V.S.

Experimental determination of volume jump on the melting of benzene
and nitrobenzene under pressure up to 10,000 kg/cm². Zhur.fiz.khim.
39 no.10:2520-2525 O '65. (MIRA 18:12)

1. Vsesoyuznyy institut fiziko-tehnicheskikh i radiotekhnicheskikh
izmereniy. Submitted August 4, 1964.

ZHOKHOVSKIY, M.K.

Thermodynamics of the melting process under pressure, Trudy inst.
Kom.stand.mer i izm.prib. no.75:69-92 '64.

(MIRA 2381)

1. Vsesoyuznyy nauchno-issledovatel'skiy institut fiziko-tehnicheskikh i radiotekhnicheskikh izmereniy.

BAKHVALOVA, V.V.; ZHOKHOVSKIY, M.K.

Experimental investigation of deformation errors of piston manometers at pressures up to 10,000 kgf/cm². Trudy inst.kom.stand.mer i izm.prib. no.75:9-27 '64.

Manometer with an effective piston area inalterable by pressure.
Ibid. 828-35 (MIRA 18:1)

1. Vsesoyuznyy nauchno-issledovatel'skiy institut fiziko-tehnicheskikh i radiotekhnicheskikh izmereniy.

BAKHVALOVA, V.V.; ZHOKHOVSKIY, M.K.

High pressure differential resistance manometer. Trudy inst. Kom.
stand.mer i izm.prib. no.75:55-59 '64.

(MIRA 383)

1. Vsesoyuznyy nauchno-issledovatel'skiy institut fiziko-tehnicheskikh i radiotekhnicheskikh izmereniy.

ZHOKHOVSKIY, M.K.; BAKHVALOVA, V.V.

Investigating a manometer with a pressure resistant effective piston surface. Izm. tekhn. no. 3124-27 Mr '64
(MIRA 17:8)

ZHOKHOVSKIY, M.K. (Moscow)

Thermodynamics of melting under pressure. Zhur. fiz. khim. 38
no.1:33-40 Ja'64. (MIRA 17:2)

1. Vsesoyuznyy nauchno-issledovatel'skiy institut fiziko-tehnicheskikh i radiotekhnicheskikh izmereniy.

ZHOKHOVSKIY, M.K.

Volume change during melting under pressure. Zhur. fiz. khim.
37 no.12:2635-2639 D '63. (MIRA 17:1)

ACCESSION NR: AP4011437

S/0076/64/038/001/0033/0040

AUTHOR: Zhokhovskiy, M.K. (Moscow)

TITLE: Thermodynamics of melting under pressure

SOURCE: Zhurnal fiz. khim., v. 38, no. 1, 1964, 33-40

TOPIC TAGS: thermodynamics, internal energy change, enthalpy, entropy, free energy, compressibility, thermal expansion, heat capacity, thermodynamic expressions, melting, melting curve

ABSTRACT: Expressions were obtained for the change in the thermodynamic parameters along the melting curve. In these expressions p = pressure; T = temperature; λ = latent heat of fusion; dv = change in volume; p_0 , T_0 , λ_0 and dv_0 corresponding values at the triple point; χ and b = empirical constants. For change in internal energy:

$$\Delta U = \lambda_0 \left[\left(\frac{T}{T_0} \right)^c \left(1 - \frac{1}{c} \right) + \frac{1}{c} \right] e^{-b(T/T_0 - 1)}.$$

Card 1/4

ACCESSION NR: AP4011437

$$\Delta U = \left[\frac{\lambda_0}{\Delta v_0} + (c - 1) p \right] \Delta v_0 e^{-b \left[\left(\frac{cp + \lambda_0 / \Delta v_0}{\lambda / \Delta v_0} \right)^{1/c} - 1 \right]}$$

for enthalpy:

$$\Delta H = \left(\frac{\lambda_0}{\Delta v_0} + cp \right) \Delta v_0 e^{-b \left[\left(\frac{\lambda / \Delta v_0 + cp}{\lambda / \Delta v_0} \right)^{1/c} - 1 \right]}$$

for entropy:

$$\Delta S = \left(\frac{\lambda_0}{\Delta v_0} \right)^{1/c} \left(\frac{\lambda_0}{\Delta v_0} + cp \right)^{1-1/c} \frac{\Delta v_0}{T_0} e^{-b \left[\left(\frac{\lambda / \Delta v_0 + cp}{\lambda / \Delta v_0} \right)^{1/c} - 1 \right]}$$

for free energy:

$$\Delta F = -p \Delta v_0 e^{-b \left[\left(\frac{\lambda / \Delta v_0 + p}{\lambda / \Delta v_0} \right)^{1/c} - 1 \right]}$$

The thermodynamic functions have extremes. Experimental data for sodium and aniline are in good agreement with theory. Expressions were obtained relating the differences in compressibilities,

Card 2/4

ACCESSION NR.: AP4011437

thermal expansions ($\Delta\alpha$, $\Delta\beta$) or the liquid and solid phases with the differences in heat capacities:

$$\Delta C_p = \Delta\chi \left[\frac{c-1}{T} - \frac{b}{T_0} + \frac{\Delta\beta}{\Delta\nu} \right].$$

$$\Delta C_p = \lambda_0 \left(\frac{T}{T_0} \right)^c e^{-b(T/T_0-1)} \left[\frac{c-1}{T} - \frac{b}{T_0} + \frac{\Delta\beta}{\Delta\nu_0} e^{b(T/T_0-1)} \right].$$

$$\Delta C_p = \frac{\lambda_0}{\Delta\nu_0} \left(\frac{T}{T_0} \right)^c \frac{1}{T} \left[(c-1-2b) \frac{T}{T_0} \right] \Delta\nu_0 e^{-b(T/T_0-1)} - \Delta\alpha \frac{\lambda_0}{\Delta\nu_0} (T/T_0)^c.$$

A differential equation for the melting curve expressed through these differences was derived:

$$\frac{dp}{dT} = -\frac{1}{\Delta\alpha} \left[\frac{b}{T_0} \Delta\nu_0 e^{-b(T/T_0-1)} + \Delta\beta \right].$$

Orig. art. has: 37 equations and 5 figures.

Card 3/4

ACCESSION NR: AP4011437

ASSOCIATION: Vsesoyuzniy nauchno-issledovatel'skiy institut
riziko-tehnicheskikh i radiotekhnicheskikh izmereniy (All Union
Scientific Research Institute of Physico-technological and Radio-
technological Measurements)

SUBMITTED: 13Jul62

DATE ACQ: 14Feb64

ENCL: 00

SUB CODE: PH

NO REF SOV: 004

OTHER: 003

Card 4/4

ZHOKHOVSKIY, Vsevolod Vatslavovich; MARASULOV, Sharif Rasulovich;
VARSHAVSKAYA, L.V., red.; EISHYREVA, G.G., tekhn. red.

[Assembly and installation of machinery in cotton-spinning
factories] Montazh mashin khlopkopriadiil'nogo proizvodstva.
Moskva, Gizlegprom, 1963. 239 p. (MIRA 16:9)
(Cotton machinery)

ZHOKHOVSKIY, V.V., kand.tekhn.nauk

Altered design of the LV-2-32 draw frame, Tekst.prom. 21
no.2:61-63 Ja '61. (MIRA 14:3)
(Spinning machinery)

BUDNIKOV, V.I.; ZHOKHOVSKIY, V.V.

New method of cotton spinning. Izv.vyz.ucheb.zav.;tekhn.tekst.prom.
no.5:55-60 '60. (MIRA 13:11)

1. Tashkentskiy tekstil'nyy institut.
(Cotton spinning)

ZHOKHOVSKIY, V.V.

Apparatus for determining the degree of straightness of the fiber in
sliver and roving. Izv.vys.ucheb.zav.;tekhn.tekst.prom. no.2:46-50
160; (MIRA 13:11)

1. Tashkentskiy tekstil'nyy institut.
(Spinning machinery) (Textile fibers--Testing)

ZHOKHOVSKIY, M.K.; BAKHVALOVA, V.V.

High-pressure differential resistance manometer. Izm.tekh. no.3:
12-15 Mr '60. (MIRA 13:6)
(Manometer)

10.4000A

28(3)

69183
S/115/60/000/03/007/031
D002/D002

B AUTHOR:

Zhokhovskiy, M.K., Bakhvalova, V.V.

TITLE: High-Pressure Resistance Differential Pressure Gauge

PERIODICAL: Izmeritel'naya tekhnika, 1960, Nr 3, pp 12-15 (USSR)

ABSTRACT: The article contains the description of a differential pressure gauge³ (Figure 1) whose application was treated previously by M.K. Zhokhovskiy [Ref 1], as well as some investigations carried out with this gage. It consists of two transmitters and two resistance coils, both ends of which are lead out through conical electric inlets, the cavities holding the coils being connected to the sources of high-pressure, whose difference is to be measured. The coils are connected to a bridge circuit with a compensating arm (Figure 2). The differential pressure gauge can be used for direct measurements of each separate pressure, as well as for indirect determinations

Card 1/2

, 1 swing
visions per
table, and

69183

S/115/60/000/03/007/031
D002/D002

High-Pressure Resistance Differential Pressure Gauge

nation of the difference of the pressures. Its characteristic feature is that it can measure very small differences of high pressures, e.g. used with the usual bridge circuit and a conventional galvanometer it can determine differences of 0.2 kg/cm^2 at pressures of 7000 kg/cm^2 . The sensitivity of the device is such that a resistance change of 0.01 ohm causes a swing of 160 divisions on the scale, i.e. 4.2 divisions per 1 kg/cm^2 . There are 2 diagrams, 1 graph, 1 table, and 2 Soviet references.

Card 2/2

ZHOKHOVSKIY, Michail Konstantinovich; LOSKUTOV, V.I., kand.tekhn.nauk,
retingerent; VOLAROVICH, M.V., prof., doktor fiz.-matemat.nauk,
red.; ALAVERDOV, Ya.G., red.izd-va; UVAROVA, A.P., tekhn.red.

[Theory and design of instruments with unsealed pistons] Teoriia
i raschet priborov s neuplotnennym porshнем. Moskva, Gos.nauchno-
tekhn.izd-vo mashinostroit.lit-ry, 1959. 203 p. (MIR 12:12)
(Measuring instruments) (Pistons)

z HOKHovskiy, M.R.

21(0); 5(t); 6(2) PHAS: I BOOK EXPLOITATION 30V/2215

Vsesoyuzny nauchno-issledovatel'skiy institut metrologii imeni

D.I. Mendelejeva

Referaty nauchno-issledovatel'skih robot; sbornik No.2 (Scientific Research Abstracts). Collection of Articles, Mr 2) Moscow, Standardizatsiya, 1958. 139 P. 1.000 copies printed.

Additional Sponsoring Agency: USSR. Komitet standartov, mer i izmeritel'nykh priborov.

Ed.: S. V. Rebetina; Tech. Ed.: N. A. Kondrat'yeva.

PURPOSE: These reports are intended for scientists, researchers, and engineers engaged in developing standards, measures, and gauges for the various industries.

COVERAGE: The volume contains 128 reports on standards of measurement and control. The reports were prepared by scientists of institutions of the Komitet standartov, mer i izmeritel'nykh priborov pri Sovete Ministratov SSSR (Commission on Standards, Measures, and Measuring Instruments under the USSR Council of Ministers). The participating institutes are: VNIIM - Vsesoyuzny nauchno-issledovatel'skiy institut imeni D.I. Mendelejeva (All-Union Scientific Research Institute of Metrology imeni D.I. Mendelejeva) in Leninsk; Sverdlovsk branch of this institute; VNIK - Vsesoyuzny nauchno-issledovatel'skiy institut Komiteza standartov mer i izmeritel'nykh priborov (All-Union Scientific Research Institute of the Commission on Standards, Measures, and Measuring Instruments, created from VNIK) - Novosibirsk; Gausdaryavennyj institut mer i izmeritel'nykh priborov (Moscow State Institute of Measures and Measuring Instruments) October 1, 1955; VNIIPMTI - Vsesoyuzny nauchno-issledovatel'skiy institut fiziko-tekhnicheskikh radio-tehnicheskikh imennoy (All-Union Scientific Research Institute of Physico-technical and Radio-engineering Measurements) in Moscow; RGMIP - Mar'Novoselskiy institut mer i izmeritel'nykh priborov (Mar'Novoselskiy Institute of Measures and Measuring Instruments); and NGMIP - Novosibirsk State Institute of Measures and Measuring Instruments. There are no references. No personalities are mentioned. There are no references.

Studying the Effect of Temperature on the Parameters of Cone Report 56

Svetozarov, P.S. and B.A. Vandyukov. (Sverdlovsk Branch of VNIIM) Studying Hardness Distribution Around the Ball Imprint in Hardness Tests 57

Vandyukov, B.A. (Sverdlovsk Branch of VNIIM). Studying Instruments for Impact Strength Tests and Drawing up Instructions for Checking Them 57

Chernovodov, M.K. and V.M. Dymantsev (NGMIP). Standard Hydraulic Stationary Dynamometers of the Second Class for the 5 and 50 ton Ranges 58

Belyi, S. Ya. (VNIIM) Assembly and Alignment of Stationary Dynamometers for Tension and Compression Tests to 10,000 and 100,000 kgf 60

Savchenko, P.S., B.A. Vandyukov, and V.V. Skobelin (Sverdlovsk Card 12/7

28(2)

SOV/115-59-8-6/33

AUTHOR:

Zhokhovskiy, M. K.

TITLE:

A Pressure Gage With an Effective Piston Area Remaining Unchanged by Pressure.

PERIODICAL: Izmeritel'naya tekhnika, 1959, Nr 8, pp 14-15 (USSR)

ABSTRACT:

The author investigates analytically the conditions under which the effective area of an unsealed pressure gage piston is not influenced by pressure. V. N. Samoylov [Ref 1] analysed possibilities of designing pressure gages with pistons whose surfaces remained unchanged when measuring pressures. He showed that a constant piston surface may be realized only with a differential piston, while a solution of this problem is difficult or impossible with other systems. Based on his previous publications [Ref 2, 3], the author of this paper attempts to achieve a more general approach to this problem by investigating the theory of unsealed pistons. He established that equal pressures acting on the outside of a solid cylinder, or on the outside and the inside of a hollow cylinder produce displacements identical in magnitude and direction. The author concluded that the dis-

Card 1/3

SOV/115-59-8-6/33

A Pressure Gage With an Effective Piston Area Remaining Unchanged by Pressure

placements of the piston radius and of the inner radius of the cylinder, which are about equal, will be identical, if the cylinder will be loaded symmetrical-
ly by equal pressures acting on its inside and out-
side. He shows a diagram of a piston system comply-
ing with the aforementioned conditions. The piston
(1) is tightly fitted to a cylindrical insert (2)
which is ground into the housing (3) and secured by
a nut (4). The cylindrical insert contains radial
holes (5) which serve equalizing the pressures in
the gap between the piston and the insert and in the
gap between the insert and the housing. The author
expects that the pressure distributions will be iden-
tical on either side of the insert surfaces with a
steady-state motion. The solution recommended for
this problem is applicable in any system consisting
of a plain piston and a conventional cylinder, but
it may be also used for any other piston system.

Card 2/3

Future investigations will show in which way this

SOV/115-59-8-6/33

A Pressure Gage With an Effective Piston Area Remaining Unchanged by Pressure

system may be realized in practice. There are 1 diagram and 3 Soviet references.

Card 3/3

SOV/115-59-7-7/33

25(1), 28(2)

AUTHOR: Zhokhovskiy, M.K.

TITLE: The Experimental Error Determination of Piston Manometers at High Pressures

PERIODICAL: Izmeritel'naya tekhnika, 1959, Nr 7, pp 11-14 (USSR)

ABSTRACT: In three publications (Ref.1,2,3), the author investigated theoretically the errors of all kinds of piston manometers, caused by deformation of the pistons and the cylinders. A solution of this very complicated problem may be given by some approximation and therefore, experimental investigations are required. The correction formulas for different systems of piston manometers up to 2,500 kg/cm² were satisfactorily confirmed by experiments of V.N. Samoylov, (Ref.4). In this paper, solutions previously obtained are investigated experimentally for an essentially expanded pressure range. Presently, there are no manometers available whose components are not subjected to pressure deformations. Only indirect test methods may be used, since direct comparison of the manometer under investigation with such gages is not possible. In this pa-

Card 1/3

SOV/115-59-7-7/33

The Experimental Error Determination of Piston Manometers at High Pressures

per, the author applied the method of comparing the readings of two manometers by means of a special differential device. These experimental results may be used for determining the error difference which is caused by the deformation of the piston systems of the manometers to be compared. The aforementioned error of each manometer is known from theoretical calculations and, consequently, there is a possibility of connecting experimental and theoretical data. Fig.1 shows the principal parts of the experimental device. Each piston manometer is connected with its own multiplicator and one manganin manometer. The manganin manometers are connected by a valve in such a way that they may communicate if the valve is open. When the valve is closed they work separately. In this case, each manganin manometer will have the same pressure which must be determined by its corresponding piston manometer. The coils of the manganin manometers are connected to a bridge circuit in such a way that the galvanometer records directly their resistance differences. This means that the manganin manometers form a differential circuit. The tests are performed in the following way: Pressure is applied to one of the piston manometers

Card 2/3

SOV/115-59-7-1/33

The Experimental Error Determination of Piston Manometers at High Pressures

and the reading of the bridge circuit is fixed. Then the valve is used for interrupting the communication between the two manganin manometers. Both manometers are brought into equilibrium by means of the multiplicators. If the pressures created by each piston manometer are equal, then the bridge will show the previous reading. In case a pressure difference arises because of different piston system deformations, the reading of the bridge will change and the errors of the manometers to be compared are found from the differences of the new and the previous galvanometer readings. An equal-arm bridge is used with $R_0 \approx 100\text{om}$. Using the aforementioned arrangement, the author investigated various types of high-pressure piston manometers at pressures of $1,000\text{-}7,000 \text{ kg/cm}^2$. In Table 2, he presents a comparison between experimental and calculated data. These data show that the deformation error differences of manometers at pressures of $5,000\text{-}7,000 \text{ kg/cm}^2$; generally show an adequate coincidence with calculated data. As a rule, deviations are of accidental character and insignificant in magnitude. There is 1 diagram, 2 tables, 3 graphs and 4 Soviet references.

Card 3/3

ZHOKHOVSKIY, M.K.

Regularities in the melting of substances and their value in
plotting scales for measuring high pressures. Izm.tekh. no.2:
16-21 Mr-Ap '58.

(MIRA 11:3)

(Pressure--Measurement)
(High pressure research)

ZHOKHOVSKIY, M. K.

Tekhnika izmerenija davleniya i razrezheniya. Moskva, Mashgiz, 1950.
183 p. illus.

At head of title; Komitet po delam mer i izmeritel'nykh priborov.

(Technique of measuring pressure and rarefaction.)

DLC: QC165.Z5

SO: Manufacturing and Mechanical Engineering in the Soviet Union,
Library of Congress, 1953

ZHOKHOVSKIY, N.K.; RAZUMIKHIN, V.N.

Mercury melting curves in the ranges up to 20,000 kg. in sec. per
cm² used for plotting scales in measuring high pressures. Izm. tekhn.
no. 4:43-47 Jl-Ag '57.

(MLBA 10:8)

(Mercury) (Manometer)

ZHOKHOVSKIY, M.K.

Problems in plotting scales for superpressures. Izv. tekhn. no.2:
3-10 Mr-Ap '57. (MLRA 10:6)
(Pressure--Measurement)

PHASE I BOOK EXPLOITATION

SOV/3478

Zhokhovskiy, Mikhail Konstantinovich

Teoriya i raschet priborov s neuplotnennym porshnem (Theory and Design of Instruments with Unsealed Piston) Moscow, Mashgiz, 1959. 203 p. Errata slip inserted. 4,000 copies printed.

Reviewer: V.I. Loskutov, Candidate of Technical Sciences; Ed. M.P. Volarovich, Doctor of Physics and Mathematics; Professor; Ed. of Publishing House: Ya.G. Aleverdov; Tech. Ed.: A.F. Uvarova; Managing Ed. for Literature on Machine Building and Instrument Making (Mashgiz): N.V. Pokrovskiy, Engineer.

PURPOSE: The book is intended for engineers, scientists and students engaged in the study, design, or testing of instruments equipped with pistons.

COVERAGE: The book presents the theory and practical application of instruments employing a free-piston system, e.g., manometers, vacuum gauges, barometers, hydraulic testing apparatus, dynamometers, various types of scale, hardness gauges, etc. The free (unsealed) pistons described here are employed in high-pressure hydraulic actuators and gas compressors wherever a high output force is essential,

Card 1/5

Theory and Design of Instruments with Unsealed Piston

SOV/3478

and also in various types of control- and servo-mechanisms designed to control large output power by a low-power force. There are 85 figures, 22 tables, and 61 references, of which 37 are Soviet, and the remainder German and English.

TABLE OF CONTENTS:

Foreword	3
Ch. I. Piston Systems in Measuring Instruments	
1. Principle of operation of free pistons and their use in instruments	5
2. Types of piston systems in instruments	5
a) Piston systems in pressure gauges	12
b) Piston systems in instruments for load and stress testing	12
c) Piston systems in other instruments	18
3. Classification of piston systems	22
	24
Ch. II. General Equations and Methods of Solution	
4. Conditions for operating piston systems	28
5. General equations for low-pressure systems	28
6. Methods of solution for high-pressure systems	30
a) Viscosity of liquids	38
b) Deformation of piston systems	38
c) General equations	44
Card 2/5	50

Theory and Design of Instruments with Unsealed Piston

SOV/3478

Ch. III. Working-Liquid Consumption in Piston Systems	55
7. Consumption of liquid at low pressure	56
a) Systems with simple pistons	56
b) Systems with differential pistons	56
8. Liquid consumption at high pressures	58
a) Systems with simple pistons	59
b) Systems with differential pistons	59
c) Systems with simple pistons in back-pressure cylinders	59
9. Consumption of liquid in complex piston systems	66
	67
Ch. IV. Forward Piston Motion	69
10. Forward piston speed at low pressure	70
a) System with simple piston	70
b) System with differential piston	70
11. Forward piston speed at high pressure	77
a) System with simple piston	79
b) System with differential piston	79
c) System with simple piston in back-pressure cylinders	91
12. Forward piston speed in complex piston systems	97
	101

Card 3/5

Theory and Design of Instruments with Unsealed Piston

SOV/3478

Ch. V. Pressure Distribution in the Clearance Space in Simple Piston Systems	
13. Pressure distribution in the clearance space in simple piston systems	108
14. Pressure distribution in the clearance space in differential piston systems	108
15. Pressure distribution in the clearance space in simple piston systems in a back-pressure cylinder	121
Ch. VI. Rotative Motion of Piston	124
16. Rotative motion of piston at low pressure	126
a) System with simple piston	128
b) System with differential piston	128
17. Rotative motion of piston at high pressure	138
a) System with simple piston	139
b) System with differential piston	140
c) System with simple piston in back-pressure cylinders	144
	146
Ch. VII. Effective Working Volume of Piston	
18. Effective working volume of piston at low pressure	150
a) System with simple piston	151
b) Systems with differential piston	151
	154

Card 4/5

Theory and Design of Instruments with Unsealed Piston

SOV/3478

19.	Effective working volume of piston at high pressure	
a)	System with simple piston	155
b)	System with simple piston in back-pressure cylinders	156
c)	Systems with differential piston	161
20.	Method of clearance determination and applications of this method	163
a)	Hydrodynamic method of clearance measurement	169
b)	Changes in the effective working volume of piston	170
21.	Adjustment of instruments	174
a)	Corrections for changes in the effective working volume of the piston due to pressure	179
b)	Corrections for temperature	185
c)	Corrections for the hydrostatic pressure of the fluid measured	188
d)	Correction for additional friction	188
e)	Correction for gravity acceleration	190

Appendices

Bibliography

AVAILABLE: Library of Congress

Card 5/5

AC/mas
6-27-60

"APPROVED FOR RELEASE: 09/19/2001

CIA-RDP86-00513R002064910003-6

ZHOKHOVSKIY, O.V.
ZHOKHOVSKIY, O.V.

Governing warp-knitting machines by means of gauges. Leg.prom. 16
no.10:33-36 0 '56. (MIRA 10:12)
(Knitting machines)

APPROVED FOR RELEASE: 09/19/2001

CIA-RDP86-00513R002064910003-6"

ZHOKHOVSKIY, O.V., inzhener; KATSENELENBOGEN, A.M., starshiy master.

New high-speed warp knitting machine. Log.prom. 15 no.5:24-27 My '55.
(Knitting machines) (MLRA 8:7)

"APPROVED FOR RELEASE: 09/19/2001

CIA-RDP86-00513R002064910003-6

ZHOKHOVSKIY, V.V.

Straightening out cotton fibers in the drawing process. Sbor. nauch.-
issl. rab. TTI no.4:149-162 '57.
(Cotton spinning) (MIRA 11:9)

APPROVED FOR RELEASE: 09/19/2001

CIA-RDP86-00513R002064910003-6"

ZHOKHOVSKIY, V. V., Candidate Tech Sci (diss) -- "Investigation of the process of straightening out cotton fiber when stretching, and determination of the optimal parameters of the process in order to provide maximum straightening of the fiber". Tashkent, 1959. 20 pp (Min Higher Educ USSR, Moscow Textile Inst), 150 copies (KL, No 24, 1959, 136)

ZHOKHOVSKIY, V.V.

BUDNIKOV, V.I., dots.; ZHOKHOVSKIY, V.V., starshiy prepodavatel'; SHAPORENKO,
I.S., inzh.

Inaccuracies in a series of educational posters. Tekst. prom. 18
no.3:66-67 Mr '58.
(MIRA 11:3)

1. Zaveduyushchiy kafedroy pryadeniya khlopka TTI for (Budnikov)
2. Kafedra pryadeniya khlopka TTI (for Zhokhovskiy)
(Textile industry--Study and teaching)

ZHOKHOVSKIY, V.V., dotsent

Straightening of fibers during drawing and evaluation of yarn straightness. Tekst. prom. 24 no.8:26-30 Ag '64.

1. Kafedra pryadeniya khlopka Tashkentskogo tekstil'nogo instituta. (MIRA 17:10)

BUDNIKOV, V.I., kand.tekhn.nauk; ZHOKHOVSKIY, V.V., kand.tekhn.
nauk

New methods of cotton spinning with the use of a twisted silver.
Tekst. prom. 21 no.6:15-21 Je '61. (MIRA 15:2)
(Cotton spinning)

ZHOKIN, Aleksey Gavrilovich; BYCHKOVА, O.V., red.; KOROBOVA, N.D.,
tekhn. red.

[Training the trade-union activist group in an enterprise]
Obuchenie profsoiuznogo aktiva na predpriatii. Moskva,
Profizdat, 1963. 61 p. (Bibliotekha profsoiuznogo akti-
vista, no.24(72))
(MIRA 17:3)

COUNTRY	: Bulgaria	H-8
CATEGORY	:	
ABS. JOUR.	: RZKhim., No. 22 1959, No.	79126
AUTHOR	: Ivanov, D. G., Gochev, V. M., and Zholaikova, D.S.	
INST.	: Not given	
TITLE	: The Extraction of Potassium from Alkaline Syenite from a Deposit Near Svidnya Village, Sofia Oblast by the Hydrothermal Process	
ORIG. PUB.	: Khimiya i Industria (Bulgaria), 30, No 5, 199-142 (1958)	
ABSTRACT	: The possibility of extracting potassium from syenites with high alkalies content has been established. The syenites are mixed with CaO and water and treated for 6 hrs in an autoclave under a pressure of 20 atm. The oxides of potassium and aluminum which pass into solution during the decomposition of the syenites are separated by carbonation with the formation of CaCO ₃ containing small amounts of Al ₂ O ₃ . The soluble carbonates of K and Na are converted to other	

CARD: 1/2

179

1. ZHOLBATYROV, Ye.
2. USSR (600)
4. Millet
7. Growing high yields of proso millet. Dost. sel'khoz. No. 5, 1953.

9. Monthly List of Russian Accessions, Library of Congress, April 1953, Uncl.

AUTHOR: A.A. Zholdak, Engineer SOV/129-59-5-14/17

TITLE: Bright Isothermal Hardening of Springs made of the Steel
50KhFA (Svetlaya izotermicheskaya zakalka pruzhin iz
stali 50KhFA)

PERIODICAL: Metallovedeniye i Termicheskaya Obrabotka Metallov,
1959, Nr 5, p 57 (USSR)

ABSTRACT: Bright Isothermal hardening has a number of advantages compared to ordinary hardening in oil and water followed by tempering. In the case of bright hardening the surface of the components remains clean and it is not necessary to clean off any scale. Furthermore there is less warping, which eliminates the necessity of grinding and lapping of components. Bright isothermal hardening is extensively used for normal bolts and fine components made of the steel 30KhGSA. The author of this paper established the following regime of bright hardening for springs made of wire from 50KhFA steel: the springs are heated in a salt bath (100% KCl) to $860 \pm 100^{\circ}\text{C}$, and held at that temperature for 2.5 minutes plus 1/3 minute for each mm of the wire diameter. Following that the wire is cooled in a bath consisting of 100% NaOH + 5.8% Na_2CO_3

Card 1/2

SOV/129-59-5-14/17

Bright Isothermal Hardening of Springs made of the Steel 50KhFA at 330 ± 5°C; this alkali bath is intensively mixed during the process by steerer or by compressed air. The springs remain in the bath for 20 to 30 minutes. If a yellow hue and an oxide film appear at the surface of the springs the bath is deoxidized with potassium ferrocyanide (0.2 to 0.1% of the weight of the bath). On removing the springs from the alkaline bath they are cooled in water at 60 to 80 °C. Then they are passivated in a 2 to 5% aqueous solution of NaNO₂ for a duration of 10 to 15 minutes and, following that, the springs are dried at 100 to 150 °C. After treating the springs in accordance with this regime the springs have a bright surface (see photo). After repeated static tests for a duration of 200 hours no residual deformation or cracks were detected. This is a complete translation.

Card 2/2 There is 1 photo.

ZHOLDAK, S. A.

Zholdak, S. A. "Drying by infra-red rays," Sudostroyeniye, 1948, No. 6,
p. 24-26

SO: U-3264, 10 April 53, (Letopis 'Zhurnal 'nykh Statey, No. 4, 1949).

28(1); 25(1)

PHASE I BOOK EXPLOITATION

SOV/2010

Zholdak, Sergey Afanas'yevich, Yakov Yakovlevich Lychagin, and Vitaliy
Semenovich Popov

Tekhnologiya izgotovleniya elektroelementov dlya elektravtomaticheskikh ustroystv
(Manufacturing Processes for Electric Elements of Automatic Electric Systems)
Moscow, Oborongiz, 1959, 423 p. Errata slip inserted, 6,000 copies printed.

Reviewers: N.N. Ushakov, Candidate of Technical Sciences, Docent, and M.M.
Zil'bersheyd, Engineer; Ed.: S.A. Abaza, Engineer; Managing Ed.: A.I. Sokolov;
Ed. of Publishing House: G.F. Loseva; Tech. Ed.: V.P. Rozhin.

PURPOSE: This book may be useful to engineers and technicians by helping them
solve practical problems they meet in their plants, and also for vuz students
concerned with the production of electrical elements of automatic electric
apparatus.

COVERAGE: The authors discuss the design problems and manufacturing of electric
small-size machines used in automatic electric systems. They describe selsyn
generators and motors, mag-slips, servomotors and rotary transformers, and
modern methods for manufacturing the parts of these machines. They also discuss

Card 1/8

Manufacturing Processes (Cont.)

SOV/2010

the outlook for improving manufacturing methods. Chapters 1, 9, and 14 are written by S.A. Zholdak, chapters 2, 3, 4, 5, 6, 12 by Ya. Ya. Ilychagin and 7, 8, 9, 11, 13, 15 by V.S. Popov. The authors thank N.N. Ushakov, M.M. Zil'bersheyd, and S.A. Abaz. There are 45 references; 42 Soviet, 2 German and 1 English (translated into Russian).

TABLE OF CONTENTS:

Foreword	3
Introduction	5
Ch. I. General Information on the Design and Technical Requirements of Small-size Electric Machines	7
Basic technical requirements	7
Selsyns	8
Rotatable transformers (VT)	26
D-c synchronous motors	33
Servomotors	36
A-c motors without commutators	45

Card 2/8

Manufacturing Processes (Cont.)

SOV/2010

Ch. II. Casting of Electric Machine Parts	53
General information	53
Chill casting of machine parts	58
Centrifugal casting of machine parts	60
Pressure casting	63
Investment casting	71
Designing molds	73
Preparation of molds	76
Machines for casting in metal molds	79
Other casting methods	83
Quality of castings	83
Checking and testing castings	84
Removal of defects in castings	87
Trimming and preliminary machining of castings	87
Ch. III. Blanking and Stamping Operations	89
General information	89
Materials required for the stamping of machine parts	90
Blanking	97

Card 3/8

Manufacturing Processes (Cont.)	sov/2010
Stamping machine parts	99
Some problems in designing dies	113
Making dies	120
Checking the quality of dies	133
Equipment for stamping	135
Mechanization and automation of cold stamping processes	136
Ch. IV. Trimming of Parts Stamped From Electrical Steel Sheets	154
Burring	154
Heat treatment of steel sheets (tempering)	156
Cleaning steel sheets before coating with electric insulation	165
Coating of steel sheets with varnish and adhesive films	166
Ch. V. Assembly of Magnetic Cores of Electric Machines	177
Various types of stator cores and their assembly	177
Various types of rotor and armature cores and their assembly	185
Quality control during the assembly of cores	193

Card 4/8

Manufacturing Processes (Cont.)

SOV/2010

Ch. VI. Machining Electric Machine Parts	196
Machining stator cores	196
Machining selsyn frames	199
Machining selsyn mag-slip frames	203
Machining bearing casings	207
Machining of poles	215
Machining rotors and armatures	217
Machining ring-clamps of servomotor brush holders	218
Machining shafts	218
Machining servomotor commutators	219
Machining selsyn contact-rings	221
Machining servomotor brushes	221
Quality control of mechanical finishing and machining	222
Equipment and tools required for machining electric machine parts	229
Ch. VII. Anticorrosion, Current - carrying and Decorative Coatings of Electric Machine Parts	230
Nickel plating and its characteristics	234
Zinc plating with chromate passivation	243
Oxide coating of aluminum and aluminum-alloy parts	247

Card 5/8

Manufacturing Processes (Cont.)

SOV/2010

Copper plating of iron, brass, and graphite parts	250
Selection of samples and acceptance regulations	255
Dressing and painting armatures and stators with windings	262
Painting parts in an electrostatic field	264
Ch. VIII. Manufacturing Electric Machine Parts From Plastics	266
Properties of molding powders used in manufacturing of electric machine parts	267
Manufacturing servomotor commutators	275
Manufacturing selsyn commutators	283
Manufacturing of terminal boards and plates	285
Ch. IX. Winding and Assembly Operations	289
Winding and insulating excitation coils	291
Assembly of field coils in stators of servomotors and selsyns with nondetachable salient poles	297
Assembly of field coils in stators with detachable poles	297
Winding stators with nonsalient poles	298
Placing of coils in three-phase stator slots	299
Stators with two separate windings	300

Card 6/8

Manufacturing Processes (Cont.)

SOV/2010

Machine winding of stators with nonsalient poles	301
Unit method of assembling stators	304
Winding and insulating of rotors and armatures	305
Ch. X. Impregnating Electric Machine Windings With Insulation Varnishes	324
Purpose and principle of impregnation	324
Impregnation and covering of electric machine windings	330
Equipment and apparatus	334
Impregnating wound parts with silicon-organic compounds	335
Ch. XI. Mechanical Finishing of Armatures and Stators After Assembly and Impregnating Operations	340
Finishing the housing of mag-slips	340
Finishing selsyn rotors	341
Finishing servomotor armatures	342
Dynamic balancing of machine parts rotating at high speed	343
Ch. XII. Assembly of Electrical Machine Component Units	359
Assembly of servomotor brushes	359
Assembly of current-carrying cross pieces	360

Card 7/8

Manufacturing Processes (Cont.)

SOV/2010

Assembly of dampers	361
Assembly of centrifugal speed regulators	362
Ch. XIII. Assembly of Electric Machines	364
Assembly of contact-type selsyns	368
Assembly of mag-slips	370
Assembly of servomotors	372
Ch. XIV. Testing of Electric Machines	375
Routine testing of selsyns	375
Standard testing of selsyns	385
Testing of rotatable transformers	390
Testing of servomotors	398
Testing of induction motors without commutators	406
Routine testing of ST and SCh d-c electric motors	410
Ch. XV. Packing and Transportation of Electric Machines	414
Bibliography	419

AVAILABLE: Library of Congress

Card 8/8

JP/mas
8-12-59

ZHOLDAX, Sergey Afanas'yevich; BULOVSKIY, P.I., retsentent; PAVLOV, V.A.,
nauchnyy red.; SHAURAK, Ye.N., red.; TSAL, R.K., tekhn. red.

[Technology of the manufacture of small gyroscopic motors] Tekhnolo-
giia izgotovleniya malogaboritnykh giromotorov. Leningrad, Gos.
sciuznoe izd-vo sudostroit-promyshl., 1961. 266 p. (MIRA 14:7)
(Gyroscopic instruments) (Electric motors)

PHASE I BOOK EXPLOITATION

SOV/5801

Zholdak, Sergey Afanas'yevich

Tekhnologiya izgotovleniya malogabaritnykh gyromotorov (The Manufacture of Miniature Gyromotors) Leningrad, Sudpromgiz, 1961. 266 p. 4200 copies printed.

Reviewer: P. I. Bulovskiy; Scientific Ed.: V. A. Pavlov; Ed.: Ye. N. Sheurak; Tech. Ed.: R. K. Tsal.

PURPOSE: This book is intended for technical personnel in the instrument industry; it may also be useful to students specializing in instrument building in schools of higher education and secondary technical schools.

COVERAGE: Problems encountered in manufacturing parts and subassemblies for miniature gyromotors are discussed. Attention is also given to the assembling and testing of gyromotors. Tools and equipment which provide for a high degree of manufacturing accuracy are described. The presentation of material in the book follows the sequence of operations used in the machining of parts and assembly of gyromotor subunits. Advanced manu-

Card 1/7

The Manufacture of Miniature Gyromotors

SOV/5801

facturing processes are discussed and recommendations for their application to production are given. No personalities are mentioned. There are 37 references: 33 Soviet and 4 English.

TABLE OF CONTENTS:

Introduction	3
Ch. I. Gyromotor Design	
1. The gyroscope and its precession	5
2. Basic design variations of gyromotors	7
Ch. II. The Casting of Gyromotor Parts	
3. General information	19
4. Die casting of gyro casings and covers	22
5. Die construction for die casting	24
6. Casting defects and the use of molds	29
7. Centrifugal pouring of a squirrel-cage rotor	31

Card 2/7

ZHOLDAK, Sergey Afanas'evich; RUBO, L.G., retsenzent[deceased];
TSIBULEVSKIY, P.I., red.

[Repair of miniature electric machines of automatic
systems] Remont elektricheskikh mikromashin avtomati-
cheskikh ustroistv. Moskva, Energiia, 1965. 255 p.
(MIRA 18:2)

GRIGOR'YEVA, V.V.; ZHOLDAKOV, A.A.

Determination of the composition of complexes by the data of
the metal indicator method. Ukr. khim. zhur. 30 no. 1-95-102 '64.
(MIRA 17:6)

1. Kiyevskiy gosudarstvennyy universitet imeni Shevchenko.

"APPROVED FOR RELEASE: 09/19/2001

CIA-RDP86-00513R002064910003-6

ZHOLDAKOV, I. V.

"The Determination of Speech Intelligibility in a Channel with a Limited Frequency Band," Iz. Elektroprom. Slat Toka, No.12, pp 32-41, 1940

APPROVED FOR RELEASE: 09/19/2001

CIA-RDP86-00513R002064910003-6"

"APPROVED FOR RELEASE: 09/19/2001

CIA-RDP86-00513R002064910003-6

ZHOLI, V. (Artem, Primorskiy kray)

Alteration of the negative frame of the enlarger "Leningrad."
Sov.foto 18 no.11:60 N '58. (MIRA II:12)
(Photography--Enlarging)

APPROVED FOR RELEASE: 09/19/2001

CIA-RDP86-00513R002064910003-6"

ZHOLIK, A.P.

Effect of the duration of "rest" of piling on its bearing capacity. Osn. fund. i mekh. grun. 6 no. 4 s 10-11 '64.

(MJRA 17,12)

ZHOLKEVICH, A.; IVANOV, Ye.

Indices of the utilization of capital assets in industry. Top.
ekon. no.10:25-33 O '60. (MIRA 13:9)
(Russia--Industries) (Index numbers (Economics))

"APPROVED FOR RELEASE: 09/19/2001

CIA-RDP86-00513R002064910003-6

ZHOLKEVICH, A.

Problems of planning improvement. Vop,ekon. no.5:143-152 My '61.
(MIRA 14:5)

(Russia—Economic policy—Congresses)

APPROVED FOR RELEASE: 09/19/2001

CIA-RDP86-00513R002064910003-6"

ZHOLKEVICH, A.

"Production organization and labor productivity in the U.S.S.R.
industry", by S.A. Kheinman. Reviewed by A. Zholkevich. Vop.
ekon. no.12:128-132 D '61. (MIRA 14:11)
(Industrial organization) (Labor productivity)
(Kheinman, S.A.)

ZHOLIK, A.-P.

ANDON'YEV, V.L.; BAUM, V.A.; BAUMGARSEN, N.K.; BEREZIN, V.D.; BIRYUKOV, I.K.;
BIRYUKOV, S.U.; BLOKHIN, S.I.; BOBOVOY, G.A.; BULEV, M.Z.; BURAKOV,
N.A.; VERTSAYZER, B.A.; VOVK, O.M.; VORMAN, B.A.; VOSHCHININ, A.P.;
GALAKTIONOV, V.D., kand. tekhn. nauk; GENKIN, Ye.M.; GIL'DENBLAT,
Ya.D., kand. tekhn. nauk; GINZBURG, M.M.; GLIMBOV, P.S.; GODES, E.G.;
GORBACHEV, V.N.; GRZHIB, B.V.; GRECOLOV, L.F., kand. s.-kh. nauk;
GRODZENSKAYA, I.Ye.; DANILOV, A.G.; DMITRIYEV, I.G.; DMITRIYENKO,
Yu.D.; DOBROKHOTOV, D.D.; IUBININ, L.G.; DUNDUKOV, M.D.; ZHOLIK,
A.P.; ZINNOVICH, D.K.; ZIMAREV, Ye.V.; ZIMASKOV, S.V.; ZUBRIK, K.M.;
KARANOV, I.F.; KNYAZEV, S.N.; KOLEGAEV, N.M.; KOMAREVSKIY, V.T.;
KOSENKO, V.P.; KORENISTOV, D.V.; KOSTROV, I.N.; KOTLYARSKIY, D.M.;
KRIVSKIY, M.N.; KUZNITSOV, A.Ya.; LAGAR'KOV, N.I.; LGALOV, V.G.;
LIKHACHEV, V.P.; LOGUNOV, P.I.; MATSKOVICH, K.F.; MEL'NICHENKO,
K.I.; MENDALEVICH, I.R.; MIKHAYLOV, A.V., kand. tekhn. nauk;
MUSIYENA, R.N.; NATANSON, A.V.; NIKITIN, M.V.; OVES, I.S.;
OGUL'NIK, G.R.; OSIPOV, A.D.; OSMER, N.A.; PETROV, V.I.; PERYSHKIN,
G.A., prof.; P'YANKOVA, Ye.V.; RAPOPORT, Ya.D.; RENZOV, N.P.;
ROZANOV, M.P., kand. biol. nauk; ROCHEGOV, A.G.; RUBINCHIK, A.M.;
RYBACHEVSKIY, V.S.; SADCHIKOV, A.V.; SEMENTSOV, V.A.; SIDENKO, P.M.;
SINYAVSKAYA, V.T.; SITAROVA, M.N.; SOSNOVIKOV, K.S.; STAVITSKIY,
Ye.A.; STOLYAROV, B.P. [deceased]; SUDZILOVSKIY, A.O.; SYRTSOVA,
Ye.D., kand. tekhn. nauk; FILIPPSKIY, V.P.; KHALTURIN, A.D.;
TSISHEVSKIY, P.M.; CHEREKASOV, M.I.; CHERNYSHEV, A.A.; CHUSOVITIN,
N.A.; SHESTOPAL, A.O.; SHEKHTER, P.A.; SHISHKO, G.A.; SHCHERBINA,
I.N.; ENGEL', F.F.; YAKOBSON, A.G.; YAKUBOV, P.A., ARKHANGEL'SKIY,

(Continued on next card)

ANDON'YEV, V.L.... (continued) Card 2.

Ye.A., retsenzent, red.; AKHUTIN, A.N., retsenzent, red.; BALASHOV,
Yu.S., retsenzent, red.; BARABANOV, V.A., retsenzent, red.; BATUNER,
P.D., retsenzent, red.; BORODIN, P.V., kand. tekhn. nauk, retsenzent,
red.; VALUTSKIY, I.I., kand. tekhn. nauk, retsenzent, red.;
GRIGOR'YEV, V.M., kand. tekhn. nauk, retsenzent, red.; GUBIN, M.F.,
retsenzent, red.; GUDAYEV, I.N., retsenzent, red.; YERMOLOV, A.I.,
kand. tekhn. nauk, retsenzent, red.; KARAULOV, B.F., retsenzent,
red.; KRITSKIY, S.N., doktor tekhn. nauk, retsenzent, red.; LIKIN,
V.V., retsenzent, red.; LUKIN, V.V., retsenzent, red.; LUSKIN, Z.D.,
retsenzent, red.; MATRIROSOV, A.Kh., retsenzent, red.; MENDEL'YEV,
D.M., retsenzent, red.; MENKEL', M.F., doktor tekhn. nauk, retsenzent,
red.; OBREZKOV, S.S., retsenzent, red.; PETRASHEN', P.N., retsenzent,
red.; POLYAKOV, L.M., retsenzent, red.; RUMYANTSEV, A.M., retsenzent,
red.; RIYABCHIKOV, Ye.I., retsenzent, red.; STASHKOV, N.G., retsen-
zent, red.; TAKANAYEV, P.F., retsenzent, red.; TARANOVSKIY, S.V.,
prof., doktor tekhn. nauk, retsenzent, red.; TIZDEL', R.R., retsen-
zent, red.; FEDOROV, Ye.M., retsenzent, red.; SHEVIYAKOV, M.N.,
retsenzent, red.; SHMAKOV, M.I., retsenzent, red.; ZHUK, S.Ya.
[deceased], akademik, glavnnyy red.; KUSSO, G.A., kand. tekhn. nauk,
red.; FILIMONOV, N.A., red.; VOLKOV, L.N., red.; GRISHIN, M.M., red.;
ZHURIN, V.D., prof., doktor tekhn. nauk, red.; KOSTROV, I.N., red.;
LIKHACHEV, V.P., red.; MEDVEDEV, V.M., kand. tekhn. nauk, red.;
MIKHAYLOV, A.V., kand. tekhn. nauk, red.; PETROW, G.D., red.; RAZIN,
N.V., red.; SOBOLEV, V.P., red.; FERINGER, B.P., red.; FREYGOFER,

(Continued on next card)

ANDON'YEV, V.L.... (continued) Card 3.

Ye.F., red.; TSYPLAKOV, V.D. [deceased], red.; KCHABLINOV, P.H.,
tekhn. red.; GEMKIN, Ye.M., tekhn. red.; KACHEROVSKIY, N.V., tekhn.
red.

[Volga-Don; technical account of the construction of the V.I. Lenin
Volga-Don Navigation Canal, the TSimlyansk Hydroelectric Center,
and irrigation systems] Volgo-Don; tekhnicheskii otchet o stroitel'-
stve Volgo-Donskogo sudokhodnogo kanala imeni V.I. Lenina, TSim-
lianskogo gidrouzla i orositel'nykh sooruzhenii, 1949-1952; v piati
tomakh. Moskva, Gos. energ. izd-vo. Vol.1. [General structural
descriptions] Obshchee opisanie sooruzhenii. Glav. red. S.IA. Zhuk.
Red. toma M.M. Grishin. 1957. 319 p. Vol.2. [Organization of con-
struction. Specialized operations in hydraulic engineering] Orga-
nizatsiya stroitel'stva. Spetsial'nye gidrotekhnicheskie raboty.

(Continued on next card)

ANDON'YEV, V.L.... (continued) Card 4.

Glav. red. S.IA. Zhuk. Red. tuma I.N. Kostrov. 1958. 319 p.

(MIRA 11:9)

1. Russia (1923- . U.S.S.R.) Ministerstvo elektrostantsii. Byuro tekhnicheskogo otcheta o stroitel'stve Volgo-Dona. 2. Chlen-korrespondent Akademii nauk SSSR (for Akhutin). 3. Deystvitel'nyy chlen Akademii stroitel'stva i arkhitektury SSSR (for Grishin, Razin).

(Volga Don Canal--Hydraulic engineering)

ZHOLKEVICH, A. Ya.

O Novoi Khromogennoi bakterii --- *Bacterium cristallino-violaceum* - New Chromogenic Bacteria)
Mikrobiol. Zhurnal, 1, 1925 p 213
Tr. 460(2) 5 June 1953

"APPROVED FOR RELEASE: 09/19/2001

CIA-RDP86-00513R002064910003-6

"Contribution to the Problem of Variation of Lepra Cultures Subjected to X-Rayting,"
Dok.AN, 39, No.2, 1943. Central Inst. Roentgenology c1943-. Central Inst. Malaria
and Med. Parasitology.

APPROVED FOR RELEASE: 09/19/2001

CIA-RDP86-00513R002064910003-6"

Medicine - Leprosy
Medicine - Animals, Experimentation

Jul/Aug 1947

"Leprosy Inoculations on Experimental Animals," A.
A. Zhalkovich, 6 pp

"Leprosy Pathology" No 4

This article is Report No IV and discusses the effect of inoculating white rats with human leprosy. Several microphotos of the effect of leprosy on various organs of the white mice. Observations were carried out over a period of six months. Among the conclusions was the fact that the histological progress of leprosy was different in white mice from the progress in humans. The experiments lead to a new method for obtaining experimental models of human leprosy on animals.

ISSR/Medicine - Leprosy (Contd)

Jul/Aug 1947

ISSR/Medicine - Leprosy (Contd)
Medicine - Animals. The experiments were conducted at the Institute of Malaria and Medical Parasitology, Academy of Medical Sciences of the USSR (Director: Prof. N.G. Sergeyev).

24459

USSR/Medicine, Biology - Microbiology

Jan/Feb 52

"Problems of the Formation of Reactive Forms of Bacteria in the Light of O. B. Lepeshinskaya's Teaching," A. Ya. Zhokhovich, Moscow

"Uspekhi Sovrem Biol" Vol XXXII, No 1, pp 101-116

The established views of monomorphists, who deny a pheomorphic cycle of development in representatives of the order Eubacteriales, must be revised. Bacteria of this order may change into a reproductive stage characterized by hypertrophic modification of cells and formation of "polyenergidic" forms according to M. A. Peshkov or of goniadangia (I) contg

USSR/Medicine, Biology - Microbiology Jan/Feb 52

(Contd 1)

207166

generative elements (II: gonidia) which are similar to elementary virus corpuscles and from which embryonal bacteria may form. I are possibly an intermediate stage between bacteria and viruses; their formation constitutes adaptation to the environment; they may form in the human or animal body. In vitro, moderate doses of neutral salts (e.g., KNO₃) or x-rays induce formation from bacteria of ripe I, stronger doses result in gigantic I which undergo lysis, excessive doses in inhibition and miniature cells. I and II are of importance in the pathogenesis of tuberculosis and leprosy and the etiology of acute infectious diseases accompanied by fellow-traveler bacteria (III) (e.g., scarlet fever, influenza, typhus). Propagation and modification of III in this manner may lead to development of pathogenic characteristics in them.

207166

POLIKARPOV, Mikhail Sergeyevich; GERSHANOVSKIY, Ovsey Moiseyevich;
ZHOLKEVICH, Anton Yevgen'yevich; STREL'NIKOVA, M.A., red.;
PONOMAREVA, A.A., tekhn. red.

[Planning of industrial production in terms of costs] Planirovaniye proizvodstva produktsii promyshlennosti v stoimostnom vyrazhenii. Moskva, Izd-vo ekon. lit-ry, 1961. 110 p.

(Industrial management)

(MIRA 15:2)

ZHOLKEVICH, A.Ye.

Indices of the volume of output and labor productivity in
ferrous metallurgy. Stal' 20 no. 12:1137-1140 D '60.
(MIRA 13:12)
(Metallurgical plants--Accounting)

69708

SUV/81-59-9-30328

5.4100

Translation from: Referativnyy zhurnal. Khimiya, 1959, Nr 9, p 39 (USSR)

AUTHOR: Zholkevich, G.A.TITLE: The Absorption and Photoconductivity of Zinc Selenide and Telluride

PERIODICAL: Uch. zap. Vologodsk. gos. ped. in-ta, 1958, Vol 23, pp 103 - 128

ABSTRACT: The absorption spectra and the photoconductivity (Ph) of ZnSe and ZnTe films have been investigated which were prepared by sublimation or by the reaction between Zn and Se or Te in a sealed ampoule. At 292°K the longwave edge of the ZnSe absorption spectrum is at 465 m μ , and that of ZnTe at 545 m μ ; at the reduction of the temperature it shifts somewhat toward the shortwave side. The spectra of Ph for ZnSe (obtained by the reaction between Zn and Se) are clearly limited at the shortwave side, have a maximum at 460 m μ and a more gradual slope of the longwave branch; for dust-coated films of ZnSe prepared by sublimation the position of the maximum in the Ph spectrum depends

Card 1/2

69708

SOV/81-59-9-30328

The Absorption and Photoconductivity of Zinc Selenide and Telluride

on the quantity of excessive Se. The Ph spectra of ZnTe have no sharp maximum limited at the shortwave side. The effect of Cd, Hg, Cl, Ga, Cu, Ag, Mn admixtures on Ph has been investigated; the activation of Cd and Hg increases Ph of ZnSe dust and shows no effect on Ph of ZnSe obtained by the chemical method.

B. Gugel¹

Card 2/2

S/112/60/000/006/020/032

Translation from: Referativnyy zhurnal, Elektrotehnika, 1960, No. 6,
pp. 358-359, # 5.2740

AUTHOR: Zholkevich, G. A.

TITLE: Photoelectric Properties of Zinc Selenide Films Produced by Vacuum
Evaporation

PERIODICAL: Uch zap. Vologodsk. gos. ped. in-ta, 1958, No. 23, pp. 129-149

TEXT: The principal photoelectric properties of photosensitive layers in photoconductive tubes are discussed, using ZnSe as an example. Methods of obtaining specimens of photosensitive layers on signal plates of photoconductive tubes are considered. The author gives the volt-ampere characteristics of two specimens, prepared by the method of vacuum evaporation with an excess of Se, and by applying ZnSe to a pure Se layer. The effect of a strong field causing a divergence from Ohm's law for a photosensitive layer at voltages of 2-4 v is investigated as well as the character of dependence of conductivity on voltage. The spectral distribution of photoelectric current is shown in case the layer is illuminated from the side of the platinum electrode. To clarify the nature ←

Card 1/2

S/112/60/000/006/020/032

Photoelectric Properties of Zinc Selenide Films Produced by Vacuum Evaporation

of the space charge, originating during polarization, time characteristics of charging and discharging the specimens have been recorded. Under steady-state conditions, at an illumination of several hundred lux, the photoelectromotive force amounts to some tenths of a volt.

V. P. Shch.

Card 2/2

ZHOLKEVICH, G. A., Cand Phys-Math Sci (diss) -- "Optical and photoelectric properties of zinc selenide and telluride". Leningrad, 1960. 17 pp (State Order of Lenin Optical Inst im S. I. Vavilov), 150 copies (KL, No 11, 1960, 128)